

EIGENSCHAPPEN / CARACTÉRISTIQUES




Glijkanaal 6 mm
Voor middelzware tot zware gordijnen
Profiellengte 600 cm

Profielgewicht 234 g/m
Extrusie volgens EN-755-9
Legering volgens EN AW-6060 T66


Profil large 6 mm
Pour des rideaux de poids moyens ou lourds
Longueur du profil 600 cm

Poids du profil 234 g/m
Extrusion selon EN-755-9
Alliage selon EN AW-6060 T66

AFMETINGEN / MESURES




PLAFONDMONTAGE / MONTAGE PLAFOND




2011

MUURMONTAGE / MONTAGE MURAL




3011



3222

Afstand tussen de steunen: 150 cm
Distance entre supports: 150 cm



Winkelhaak + steun
Equerre + support



	X =	H =
3051 + 2011	6,4 cm	4,0 cm
3061 + 2011	8,9 cm	4,0 cm
3071 + 2011	11,4 cm	4,0 cm
3081 + 2011	16,4 cm	4,0 cm

VERBUIGINGEN / COURBURES



R1 = 20 cm
R1 = 20 cm
/



X = 30 cm (geen binnenbocht)
X = 30 cm (pas de courbure intérieure)
/



/
/
/

Horizontaal
Horizontal
Verticaal / Verticale

KLEUREN / COULEURS



Aluminium geanodiseerd
Aluminium anodisé
-00



Wit gelakt
Blanc laqué
-10